

0854 ECLIPSE 3000 ACRYLIC PIGMENTED WALLCOVERING PRIMER



A premium quality, heavy-duty pigmented universal primer designed to replace all other sizing and wallcovering primers including latex and oil-based products. Helps protect drywall when removing wallcovering as well as improving slip during wallcovering installation. An opaque acrylic resin formulation with maximum moisture sensitivity resistance.

Benefits:

- Easy clean up, water based interior primer.
- Hides colors and patterns of existing wallpapers and paints.
- Use over tightly-adhering existing wallpapers to ease new installation.
- Excellent new construction primer on new drywall for application of commercial wallcoverings.

Surface Preparation and Primer Recommendations

INTERIOR

Surface	Preparation	Primer
Wood	KPS1, KPS2	KSU1
Drywall	KPS6	This Primer
Concrete / Masonry	KPS4	KSU2
CMU	KPS5	KSU2
Ferrous Metal	N.R.	N.R.
Non-Ferrous Metal	N.R.	N.R.

EXTERIOR

Not intended for exterior application.

Where to Use:

- Recommended for properly prepared interior drywall, plaster, concrete and tightly-adhering existing wallpapers.

Limitations: Not intended for use over lime containing plaster.

Colors: White, may be tinted with up to 2 fluid ounces of universal colorant to approximate the finish color.

Type/Thinner: Latex/water. This product is packaged ready to use.

Type: 100% Acrylic

Finish: Flat

Sheen: Less than 6% @ 60°

Solids by Volume: 27.56%

How to Apply:

- Stir well with lifting motion
- Apply by brush, roller or airless spray

Surface Temp: Temperature should be above 50°F and below 95°F. Avoid frost, fog and damp conditions.

Coverage: 295 ft² @ 1.5 MIL dry film

*Coverage will vary depending on application method, surface texture, porosity and color.

Drying Time: Dries to the touch in 1 hour, may be re-coated after 4 hours. Drying time will vary depending on temperature, air circulation and humidity.

VOC: Maximum of 140 g/l

Clean-Up: Clean all application equipment with soap and warm water.

*All surfaces must be sound, dry, clean and free from dirt, oil, wax grease, mildew, loose or peeling paint and other foreign material.

These suggestions and data are based on information we believe to be reliable. They are offered in good faith and limited guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them. Specifications subject to change without notice.

July 16, 2008