

118000 ENVIROKOTE ZERO VOC PRIMER / SEALER



A top quality latex pigmented primer/sealer formulated with the finest, environmentally friendly raw materials. It has been formulated for use on nearly all interior surfaces. It may be topcoated with most conventional latex or alkyd based products, but is designed for use as a system with other EnviroKote fine finishes.

Benefits:

- Green Seal Certification.
- Excellent new work primer for wood trim and drywall.
- Zero VOC make EnviroKote ideal for schools and hospital application.
- Fast drying, low odor, use under all sheens (flat to high gloss), use under water or solvent reduced finishes.
- Its use on new or repaint surfaces assures superior, uniform finish results.

Surface Preparation and Primer Recommendations

INTERIOR

Surface	Preparation	Primer
Wood	KPS1, KPS2	KSU1
Drywall	KPS6	This Primer
Concrete / Masonry	KPS4	KSU2
CMU	KPS5	KSU2
Ferrous Metal	N.R.	N.R.
Non-Ferrous Metal	N.R.	N.R.

EXTERIOR

Not intended for exterior application.

Where to Use:

- Recommended for properly prepared interior drywall, plaster, concrete or wood.

Limitations: Not intended for use over lime containing plaster, floors or decks.

Colors: White, may be tinted with up to 2 fluid ounces of universal colorant to approximate the finish color. The addition of over 2 ounces of colorant will alter the VOC content of this product.

Type/Thinner: Latex/water. This product is packaged ready to use.

Type: Vinyl Acrylic Emulsion / 100% Acrylic

Finish: Flat

Sheen: Less than 5% @ 60°

Solids by Volume: 42.49%

How to Apply:

- Stir well with lifting motion
- Apply by brush, roller or airless spray

Surface Temp: Temperature should be above 50°F and below 95°F. Avoid frost, fog and damp conditions.

Coverage: 454 ft² @ 1.5 MIL dry film

*Coverage will vary depending on application method, surface texture, porosity and color.

Drying Time: Dries to the touch in 1 hour, may be re-coated after 4 hours. Drying time will vary depending on temperature, air circulation and humidity.

VOC: 0 g/l (per EPA method)

Clean-Up: Clean all application equipment with soap and warm water.

*All surfaces must be sound, dry, clean and free from dirt, oil, wax grease, mildew, loose or peeling paint and other foreign material.

These suggestions and data are based on information we believe to be reliable. They are offered in good faith and limited guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them. Specifications subject to change without notice.

July 16, 2008