

## 316010 PREMIUM ONE EGGSHELL LATEX ENAMEL



A high quality acrylic eggshell wall and trim paint. Premium One provides enamel-like durability and wash ability while leaving a soft, subtle appearance. It features excellent hide, maximum coverage, easy flow, and low odor. Premium One's tough eggshell, non-porous film, is suitable for most areas of commercial and residential new or repaint work.

### Benefits:

- Deep, eggshell finish for walls and trim.
- Excellent wash ability and superior performance over standard flat wall finishes.
- Fast drying, low odor and soap and water clean up.
- Its use on new or repaint surfaces assures superior, uniform finish results.

### Surface Preparation and Primer Recommendations

#### INTERIOR

Surface	Preparation	Primer
Wood	KPS1, KPS2	KSU1
Drywall	KPS6	KSU3
Concrete / Masonry	KPS4	KSU2
CMU	KPS5	KSU2
Ferrous Metal	KPS7	KSU4
Non-Ferrous Metal	KPS8	KSU4

#### EXTERIOR

Not intended for exterior application.

### Where to Use:

- Recommended for properly prepared interior drywall, plaster, concrete, wood, previously painted or primed metal and exterior trim applications.

Limitations: Not intended for high humidity areas.

Colors: White and light to dark custom Color Life colors.

Type/Thinner: Latex/water. This product is packaged ready to use.

Type: Vinyl Acrylic / 100% Acrylic Emulsion

Finish: Eggshell

Sheen: 14% to 18% @ 60°

Solids by Volume: 36.41%

### How to Apply:

- Stir well with lifting motion
- Apply by brush, roller or airless spray

Surface Temp: Temperature should be above 50°F and below 95°F. Avoid frost, fog and damp conditions.

Coverage: 395 ft<sup>2</sup> @ 1.5 MIL dry film

\*Coverage will vary depending on application method, surface texture, porosity and color.

Drying Time: Dries to the touch in 1 hour, may be re-coated after 4 hours. Drying time will vary depending on temperature, air circulation and humidity.

VOC: Maximum of 150 g/l

Clean-Up: Clean all application equipment with soap and warm water.

\*All surfaces must be sound, dry, clean and free from dirt, oil, wax grease, mildew, loose or peeling paint and other foreign material.

These suggestions and data are based on information we believe to be reliable. They are offered in good faith and limited guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them. Specifications subject to change without notice.

July 16, 2008