



## 8300 ACCU-GUARD 100% ACRYLIC INTERIOR / EXTERIOR DTM HIGH GLOSS FINISH

Our high gloss (Direct to Metal) 100% Acrylic with the appearance and performance that is normally associated with alkyd enamels. The excellent flow and a high gloss finish allow it to be used in place of alkyd enamels where a low V.O.C. product is preferred. Accu-Guard DTM waterborne products provide easy application and clean up with the performance and durability of an alkyd finish. This product has excellent adhesion over properly prepared aged alkyd films, interior wood, and metal surfaces.

### Benefits:

- Smooth high gloss finish.
- Excellent adhesion on metal surfaces.
- Fast drying, low odor and soap and water clean up.
- Its use on new or repaint surfaces assures superior, uniform finish results.

### Surface Preparation and Primer Recommendations

#### INTERIOR

Surface	Preparation	Primer
Wood	KPS1, KPS2	KSU1
Drywall	KPS6	KSU3
Concrete / Masonry	KPS4	KSU2
CMU	KPS5	KSU2
Ferrous Metal	KPS7	KSU4
Non-Ferrous Metal	KPS8	KSU4

#### EXTERIOR

Surface	Preparation	Primer
Wood	KPS9	KSU1
Drywall	KPS14	KSU7
Concrete / Masonry	KPS12	KSU5
CMU	KPS13	KSU5
Hardboard Siding	KPS10	KSU6
Cementitious Siding	KPS11	KSU6
Ferrous Metal	KPS15	KSU4
Non-Ferrous Metal	KPS16	KSU4

\*All surfaces must be sound, dry, clean and free from dirt, oil, wax grease, mildew, loose or peeling paint and other foreign material.

These suggestions and data are based on information we believe to be reliable. They are offered in good faith and limited guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them. Specifications subject to change without notice.

July 16, 2008

### Where to Use:

- Recommended for properly prepared interior and exterior previously painted or primed metal applications.

Limitations: Not intended for high humidity areas, floors or walkways.

Colors: White and light to dark custom Color Life colors.

Type/Thinner: Latex/water. This product is packaged ready to use.

Type: 100% Acrylic Resin

Finish: High Gloss

Sheen: 75% to 85% @ 60°

Solids by Volume: 36.85%

### How to Apply:

- Stir well with lifting motion
- Apply by brush, roller, airless and conventional spray.

Surface Temp: Temperature should be above 50°F and below 95°F. Avoid frost, fog and damp conditions.

Coverage: 390 ft<sup>2</sup> @ 1.5 MIL dry film

\*Coverage will vary depending on application method, surface texture, porosity and color.

Drying Time: Dries to the touch in 1 hour, may be re-coated after 4 hours. Drying time will vary depending on temperature, air circulation and humidity.

VOC: Maximum of 250 g/l

Clean-Up: Clean all application equipment with soap and warm water.