

## 8400 AMBASSADOR 100% ACRYLIC INTERIOR / EXTERIOR GLOSS ENAMEL

Our high quality, extremely durable, chalk-resistant, 100% acrylic finish for a wide variety of exterior and interior surfaces. It dries to a smooth gloss finish. Our best interior/exterior gloss finish. Its formulation provides improved block resistance over typical acrylic paints.

### Benefits:

- Non-yellowing, washable and stain resistant.
- Ideally suited for commercial and residential use.
- Excellent sheen and color retention.
- Easy to apply with soap and water clean up.
- Exceptional maintenance capability.

### Surface Preparation and Primer Recommendations

#### INTERIOR

| Surface            | Preparation | Primer |
|--------------------|-------------|--------|
| Wood               | KPS1, KPS2  | KSU1   |
| Drywall            | KPS6        | KSU3   |
| Concrete / Masonry | KPS4        | KSU2   |
| CMU                | KPS5        | KSU2   |
| Ferrous Metal      | KPS7        | KSU4   |
| Non-Ferrous Metal  | KPS8        | KSU4   |

#### EXTERIOR

| Surface             | Preparation | Primer |
|---------------------|-------------|--------|
| Wood                | KPS9        | KSU1   |
| Drywall             | KPS14       | KSU7   |
| Concrete / Masonry  | KPS12       | KSU5   |
| CMU                 | KPS13       | KSU5   |
| Hardboard Siding    | KPS10       | KSU6   |
| Cementitious Siding | KPS11       | KSU6   |
| Ferrous Metal       | KPS15       | KSU4   |
| Non-Ferrous Metal   | KPS16       | KSU4   |

\*All surfaces must be sound, dry, clean and free from dirt, oil, wax grease, mildew, loose or peeling paint and other foreign material.

These suggestions and data are based on information we believe to be reliable. They are offered in good faith and limited guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them. Specifications subject to change without notice.

July 16, 2008

### MPI 114

#### Where to Use:

- Recommended for properly prepared new or repaint work on interior or exterior plaster, gypsum board, masonry, concrete, wood, and metal.

Limitations: Not intended for use over lime containing plaster without proper sealing, floors or decks.

Colors: White and light to dark custom Color Life colors.

Type/Thinner: Latex/water. This product is packaged ready to use.

Type: 100% Acrylic Resin

Finish: High Gloss

Sheen: 80% + @ 60°

Solids by Volume: 38.43%

#### How to Apply:

- Stir well with lifting motion
- Apply by brush, roller or airless spray

Surface Temp: Temperature should be above 50°F and below 95°F. Avoid frost, fog and damp conditions.

Coverage: 400 ft<sup>2</sup> @ 1.5 MIL dry film

\*Coverage will vary depending on application method, surface texture, porosity and color.

Drying Time: Dries to the touch in 2 hours, may be re-coated after 4 hours. Drying time will vary depending on temperature, air circulation and humidity.

VOC: Maximum of 190 g/l

Clean-Up: Clean all application equipment with soap and warm water.