

PRIMER SELECTIONS WOOD - INTERIOR / EXTERIOR



0890 Accu-Pro Sandable Drywall Primer MPI 50

Our high quality latex primer specifically formulated for use under eggshell, satin, semi-gloss, or gloss finishes. Accu-Pro Sandable Drywall Primer 0890's high-hide formula makes it an ideal product for prepping and sealing smooth finished drywall and wood trim.

Recommended Surfaces: Gypsum Board, Wood, MDF - Interior

348JB Acrylic Enamel Undercoat

A good quality acrylic latex enamel undercoat designed for use on most interior surfaces. Easy to use with good leveling properties and excellent holdout characteristics. May be topcoated with latex or alkyd finishes. This product is suited for use in residential and commercial applications, where higher sheen or premium finish coats will be used.

Recommended Surfaces: Gypsum Board, Wood, MDF, Plaster, Concrete, CMU - Interior

4003 Embassy Cancel Alkyd Primer / Sealer

A fast drying, alkyd, stain killing primer formulated for use on most interior surfaces. It will block many common household stains including pen, pencil, water and smoke damage. For maximum blocking of oily or grease stains, a water-based topcoat is recommended (5011 X-Terminator II). One coat will block most stains. Severe stains and solvent sensitive stains may require a second coat or a shellac based sealer.

Recommended Surfaces: Gypsum Board, Wood, MDF, Plaster, Concrete, CMU - Interior

4011 X-Terminator Alkyd Primer / Sealer

A quick drying alkyd, interior primer with exceptional sealing, adhesion and stain killing / blocking properties. Recommended for use on drywall, plaster, wood, hardboard, and previously painted interior walls, ceilings and trim. Will block stains, seal surfaces and provide excellent adhesion on most substrates.

Recommended Surfaces: Gypsum Board, Wood, MDF - Interior

4048 Wood Kraft Fast Dry V.T. Interior Satin Sealer / Finish MPI 102

A combination of quick drying sanding sealer and clear satin varnish for interior wood surfaces. When used as a multiple coat system, it gives good depth and enhances the natural grain and color of the wood. Not recommended as a sealer under urethanes, lacquer or on bar tops and floors. Fast dry, easy sanding and rich finish provides a "one container" finishing system. Will not lift or cause wrinkling of old finishes. Multiple coats may be applied in one day.

Recommended Surfaces: New wood - Interior

These suggestions and data are based on information we believe to be reliable. They are offered in good faith and limited guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them. Specifications subject to change without notice.