

KSU6

PRIMER SELECTIONS - EXTERIOR HARDBOARD / CEMENTITIOUS SIDING



5011 X-Terminator II Water Borne Primer / Sealer

Quick drying interior/exterior primer with exceptional sealing, adhesion and stain killing/blocking properties. Recommended for use on drywall, plaster, hardboard, masonry, wood and previously painted interior walls, ceilings and trim. Will block stains, seal surfaces and provide excellent adhesion on most substrates.

Recommended Surfaces: Gypsum Board, Wood, MDF, Plaster, Concrete, CMU - Interior and Exterior

5807 Accu-Shield 100% Acrylic Epoxy Modified Concrete Primer

An epoxy modified 100% acrylic resin primer / sealer for concrete. The epoxy modification offers increased resistance to efflorescence (soluble salts), water and wear. The combined resin systems assist in tying down loose chalk and improving intercoat adhesion (100% acrylic topcoat is recommend). This coating exhibits outstanding performance over concrete and structural masonry surfaces. Outstanding for use on new tilt-up concrete structures.

Recommended Surfaces: Plaster, Concrete, Masonry, CMU - Exterior

5862 Embassy-WB Cancel 100% Acrylic Primer MPI 6,39

An extremely versatile 100% Acrylic Primer. This breathing-type latex primer retains its flexibility to form a perfect foundation for all types of finishes. Embassy is specially formulated to sand quickly after application. It is a water reducible, alkali resistant, fast-drying primer. May be top-coated with most finishes, water or solvent-reduced. The flat finish is ideal for easy application of the finish coat and develops excellent adhesion to most properly prepared surfaces.

Recommended Surfaces: Gypsum Board, Wood, MDF, Plaster, Concrete, CMU - Interior and Exterior

5940 Accu-Guard 100% Acrylic Interior / Exterior Block Filler MPI 4

An exceptional ready-mixed block filler. The 100% acrylic resin formulation provides a smooth uniform finish with very good light to moderate moisture resistance. One coat allows finish coats to spread further per gallon versus the spread rate that would be achieved over an unfilled substrate. It has good holdout and may be top-coated with most finish paints such as acrylics, alkyds, and water or solvent borne epoxies. Especially resistant to the alkalinity often present in masonry.

Recommended Surfaces: Plaster, Concrete, CMU - Interior and Exterior

These suggestions and data are based on information we believe to be reliable. They are offered in good faith and limited guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them. Specifications subject to change without notice.